



**Peristaltic C**      **Peristaltic Pumps**  
 v x Q B B S F d      u v x Q m



l/h (1.56 US Gal/h),  
 pres s Q r Q bar (14 psi)  
 flow rates up to 6 l/h (1.56 US Gal/h),  
 pressure up to 1 bar (14 psi)

dimension o U dimensions: 81 x 56 x 80 mm

dimension o U dimensions: 111 x 56 x 80 mm

l/h - US Gal/h	Pres s Q bar - psi	F Silicone <sup>®</sup> /Santoprene <sup>®</sup>	F Santoprene <sup>®</sup> NSF <sup>®</sup>	F-T Silicone <sup>®</sup> /Santoprene <sup>®</sup>	F-T Santoprene <sup>®</sup> NSF <sup>®</sup>	120V, 24Vdc/Vac
3 0 3 / 2 0 4	3 / 3 6	61 80	79 31	74 16	82 40	-20
4 0 4 / 2 0 7	3 / 3 6	61 80	79 31	74 16	82 40	20
5 0 5 / 2 0 9	3 / 3 6	61 80	79 31	74 16	82 40	
6 0 6 / 3 0 3	8 3 / 3 6	71 07	90 64			solo only 4 6 7h l
8 0 2 / 3 0 7	8 3 / 3 6					solo only 4 6 7h l

**F NSF<sup>®</sup>**  
 La l C z o s U v m C L C m C n Q p s t Q [ n s U Q s l l m o v 2 2 v x 1 2 3 0 v a l 2 3 0 v c o n t u b o i n S a n t o p r e n e Q o S i l i c o n C v e r s i o n 4 4 p 0 l/h c o n a l i m e n t a z i o n e 2 4 V d c . I t u b o o U p s t Q C C " x T o n C h m e d i a n t e C o m Q o m n i c o T o s x . ' v m " o z Q n o v C l C o x o v m " Q l o o x m " , o x U C p s t Q C C T o n v C m C C o n s Q v V a p a n e r s n T c v s m C o U s x n o z o x n s o x b Q C C [ z " o n o l o T p C n s v Q x b l o z C C D  
 Disponibile con certificazioni NSF.  
 Peristaltic pump F series has a constant flow rate, available 1,1, 2,2 and 3,3 l/h at 230V with Santoprene<sup>®</sup> or silicone tubing, model 4.4 and 6.0 l/h only 24Vdc. The tube is coupled to the external fitting with a SS clamps. The cover is anchored on the casing with 3 screws, on it there's a groove for an additional shaft support. The hydraulic head is independent of the motor type and can be supplied separately. Inter-axis holes: 42 mm - 1,65"; anchoring panel thickness measure from 1 to 4mm - 0,04 to 0,16". Available NSF certified version.

**F-T NSF<sup>®</sup>**  
 solo con alimentazione 120-230V / don reg " v C n s e p o r i z Q C e v m C n Q 7 3 s e c . S U Q s l v o m Q m o T e p s m C n s Q T 5 1  
 Same characteristics as the F series peristaltic pump with 120-230V power supply with temporised flow control through potentiometer timer setting between 0 ÷ 7 sec. Available NSF certified version.

