

Accesorios
bomba peristaltica

Accessories
peistaltiqumps

F

Santopreno® - RTU 00008 01 -
Silicono® - RTU 00008 02 -

Tubo Completo /Compleet Hose

TUBO COMPLETO (Santopreno®) para bomba 1.1 l/h, 2.2 l/h, 4.4 l/h, 6.6 l/h - Ø 4x7 mm
COMPLETE HOSE (Santopreno®) for 1.1 l/h, 2.2 l/h, 4.4 l/h, 6.6 l/h pump - Ø 4x7 mm



B-F/V/EV/FCD

Santopreno® - RTU 00011 01 -
Silicono - RTU 00011 02 -

Tubo Completo /Compleet Hose

TUBO COMPLETO (Santopreno®) para bomba 10,6 e 4 l/h - Ø 6x9 mm
COMPLETE HOSE (Santopreno®) for 10, 6 and 4 l/h - Ø 6x9 mm



SERIE B-F/V

Santopreno® - RTU 00013 01 -
Silicono - RTU 00013 02 -

Tubo Completo /Compleet Hose

TUBO COMPLETO (Santopreno®) para bomba 2, 3 l/h; Ø 4.8x9.6 mm
COMPLETE HOSE (Santopreno®) for 2, 3 l/h; Ø 4.8x9.6 mm



SERIE B-F/V

Santopreno® - RTU 00012 01 -
Silicono - RTU 00012 02 -

Tubo Completo /Compleet Hose

TUBO COMPLETO (Santopreno®) para bomba 1 l/h; Ø 3.2x9.6 mm
COMPLETE HOSE (Santopreno®) for 1 l/h; Ø 3.2x9.6 mm



SERIE B-H

B-H 22-1

Tubo Completo /Compleet Hose

8,0X12,8 CM22,0 Norprene® - STU 00017 03 -
8,0X12,8 CM22,0 Santopreno® - STU 00017 01 -
8,0X12,8 CM22,0 Silicono - STU 00017 02 -

Tubo completo en diversos materiales.
Tube in different materials



B-H 30-1/40-1/65-1/100-1

9,6X15,9 CM28,0 Norprene® - STU 00019 13 -
9,6X15,9 CM28,0 Silicono - STU 00019 15 -

KIT DE DETERGENCIA EPDM

SCO 00002 02 -

EPDM DETERGENT ACCESSORIES

Kit en EPDM para detergente en bomba peristaltica: 4m tubo PVC cristal (4x6mm), record de inyeccion 90°, filtro de fondo EPDM.
EPDM peristaltic pumps detergent accessories: 4m PVC crystal tube (4x6mm), 90° injection nipple for free discharge, stainless steel foot filter with EPDM check valve.



KIT DE ABRILLANTADOR FPM

SCO 00003 01 -

FPM BRIGHTNER ACCESSORIES

Kit en FPM para abrillantador en bomba peristaltica: 3m tubo polietileno (4x6mm), 2m tubo PVC cristal (4x6mm), valvula inyeccion, filtro de fondo en FPM.
FPM peristaltic pumps brightner accessories: 3 m polyethylene tube (4x6mm), 2m PVC crystal tube (4x6mm), nickel plated brass ball injection valve, stainless steel foot filter with FPM check valve.



KIT DE TRATAMIENTO DE AGUA

SCO 00007 01 -

FPM WATER TREATMENT ACCESSORIES

Kit en FPM para el tratamiento del agua en bomba peristaltica: 2m tubo polietileno (4x6mm), 2m tubo PVC cristal (4x6mm), valvula inyeccion PVC 3/8" con valvula FPM, filtro de fondo en PP.
FPM peristaltic pumps water treatment accessories: 2 m polyethylene tube (4x6mm), 2m PVC crystal tube (4x6mm), 3/8" PVC-FPM injection valve, PP foot filter without check valve



VALVULA DE INYECCION PARA DETERGENTE
DETERGENT INJECTION VALVE

DRA 00069 01 -



Racord de inyeccion de 90°, 12 mm.
90° injection nipple for free discharge, 12 mm.

VALVULA DE INYECCION PARA ABRILLANTADOR
BRIGHTNER INJECTION VALVE

21 440 04 -



Valvula de inyeccion para abrillantador para dosificacion en boiler 1/8" GM. ("O" ring FPM - Viton®, esfera inox).
Brightner 1/8" GM injection valve to dose into boiler. nichel plated brass ("O" ring FPM - Viton®, stainless steel ball).

VALVULA DE INYECCION EN PVC
PVC INJECTION VALVE

FPM (Viton®) - 21 440 32 -
EPDM (Dutral®) - S/A 00059 01 -



valvula inyeccion en PVC 3/8" con valvula de labio anti-retorno.
3/8" PVC injection valve, check valve inclusive.

FILTRO DE FONDO
SS FOOT FILTER

EPDM (Dutral®) - 21 420 29 -
FPM (Viton®) - 21 420 28 -
Silicona - 21 420 26 -



Filtro di fondo con, o sin valvula.
Stainless steel foot filter with or without check valve.

Sin valvula / Without valve - 21 420 27 -

DOSIFICADOR ABRILLANTADOR A PRESION
HYDRAULIC RINSE-AID PUMP

1 PDD 001 -



Esta bomba funciona utilizando la presion debida de la propia maquina. Dosificador hidraulico a presion de 0 a 3 cm³/ciclo.
Hydraulic pump, activated by water pressure, each time the machine rinse to add a brightner product.
Adjustment from 0 to 3 cm³/cycle.

SONDA DE CONDUCTIVIDAD
CONDUCTIVITY PROBE

400÷20.000µS 1/2" GM PVC - 21 380 04 -



Sonda de conductividad con 2 electrodos AISI 316, y constante de celda K=1 para bomba dosificadora B-FCD. 2 metros cable
Conductivity electrode with two stainless steel sensors AISI 316 Cell constant k=1 suitable for B-FCD dosing pump. 2 mt - 6,6 feet cable